



**ATVS UTVS**

**ADVENTURE**

**ABOUT US**

**ABOUT US**

WWW.FANGPOWER.COM

EMAIL: sales@fangpower.com

MOBILE: +86 13954494134

ADDRESS: No.10, North Zone, Zibo Comprehensive Bonded Zone, High-tech Zone, Zibo City, Shandong Province



## ATV

SW680L/880L/1000L MAX MUD	01
SW680/880/1000VV	03
SW580L/680L/880L/1000L PRO	05
SW580S/680S PLUS	07
SW580EL/680EL	09
SW580ES/680ES	11
SW580/680L-1 POWERMAX	13
SW680 MUD POWERMAX	15
SW250 BIG BULL	17
SW200 BIG BULL	19
SW125-1 OUTLAW/125-2 MARS/125-3 SPORT	21

## UTV

FX400 PREDATOR	23
FX400XL PREDATOR	25
FX400U FARMER	27
FX400 SNOWMOBILE	29
FX250-2 SPIDER	31
FX250 DICTATOR	33
FX200 TIGER	35

## EV/ENGINE

EV POWERMAX	37
EV PREDATOR	39
SW400/500/600CC	41
SW800/1000CC	43

2026 **GB3** **THRAX**

# SW680L/880L/1000L MAX MUD

► ENGINE SW680/880/1000L MAX

ENGINE TYPE	Single-Cylinder, 4-Stroke Liquid-Cooled, 4 Valves (680) V-twin, water-cooled, 4-stroke, SOHC, 4 valves/cylinder (880/1000)
DISPLACEMENT	580CC/800CC/976CC
MAX POWER/RPM	34kw/46hp@6500rpm 50kW/68hp@7000rpm 66kw/90hp@7200rpm
MAX TORQUE	51N·m(6000r/min) 72N·m@6000rpm 95N·m@6000rpm
FUEL SUPPLY	Bosch Efi
TRANSMISSION	Cvt
STARTING TYPE	Electric Start
GEAR SHIFT /ORDER	Manually/ L-H-N-R-P



680L MAX	880L MAX	1000L MAX	680/880/1000L MAX	680L MAX	680L MAX	880/1000L MAX	880/1000L MAX
<b>46HP</b>	<b>68HP</b>	<b>90HP</b>	<b>100KM/H</b>	<b>430KG</b>	<b>502KG</b>	<b>465KG</b>	<b>537KG</b>
HORSEPOWER	HORSEPOWER	HORSEPOWER	MAX SPEED	DRY WEIGHT	GROSS WEIGHT	DRY WEIGHT	GROSS WEIGHT

► DIMENSIONS SW680/880/1000L MAX

LENGTH X WIDTH X HEIGHT	2330×1240×1495mm (680) 2330×1270×1520mm (880/1000)
WHEELBASE	1470mm
Seat Height	910mm
Front/Rear Track	990mm /940mm
GROUND CLEARANCE	290mm (680) 330mm (880/1000)

► CHASSIS SW680/880/1000L MAX

DRIVE SYSTEM	2WD/4WD/Front differential lock EPS
FRONT /REAR SUSPENSION	Double A-arm independent suspension
Front/Rear Shock Absorber	Adjustable nitrogen shock absorbers
Front/Rear Brakes	Front and rear hydraulic disc
FRONT TIRES, REAR TIRES	27×9-14, 27×11-14 (680) 29×9-14, 29×9-14 (880/1000)
RIM	Front: 14×7.0 Rear: 14×8.5

► OTHER FEATURES SW680/880/1000L MAX

FUEL CAPACITY(L/GAL)	20L (680) 25L (880/1000)
BATTERY CAPACITY	12V32Ah
PACKAGE SIZE (MM)	2300×1300×1300mm
LOADING QUANTITY (PCS)	40HQ : 18PCS



# 2026 **GBB** **THRAX** SW680/880/1000V V

## ► ENGINE SW680/880/1000V V

ENGINE TYPE	Single-Cylinder , 4-Stroke Liquid-Cooled, 4 Valves (680) V-twin, water-cooled, 4-stroke, SOHC, 4 valves/cylinder (880/1000)
DISPLACEMENT	580CC/800CC/976cc
MAX POWER/RPM	34kw/46hp@6500rpm 50kw/68hp@7000rpm 66kw/90hp@7200rpm
MAX TORQUE	51N·m(6000r/min) 72N·m(6000r/min) 95N·m@6000rpm
FUEL SUPPLY	Bosch Efi
TRANSMISSION	Cvt
STARTING TYPE	Electric Start
GEAR SHIFT /ORDER	Manually/ L-H-N-R-P



680V V

**46**HP

HORSEPOWER

680V V

**100**KM/H

MAX SPEED

880V V

**68**HP

HORSEPOWER

880V V

**100**KM/H

MAX SPEED

1000V V

**90**HP

HORSEPOWER

1000V V

**100**KM/H

MAX SPEED

## ► DIMENSIONS SW680/880/1000V V

LENGTH X WIDTH X HEIGHT	2330×1240×1600mm (680) 2360×1270×1600mm (880/1000)
WHEELBASE	1470mm
Seat Height	910mm
Front/Rear Track	990mm /940mm
GROUND CLEARANCE	300mm

## ► CHASSIS SW680/880/1000V V

DRIVE SYSTEM	2WD/4WD/Front differential lock EPS
FRONT /REAR SUSPENSION	Double A-arm independent suspension
Front/Rear Shock Absorber	Hydraulic damping spring adjustable shock absorber
Front/Rear Brakes	Front and rear hydraulic disc
FRONT TIRES, REAR TIRES	26×9-14, 26×11-14
RIM	Front: 14×7.0 Rear: 14×8.5

## ► OTHER FEATURES SW680/880/1000V V

FUEL CAPACITY(L/GAL)	20L (680) 25L (880/1000)
BATTERY CAPACITY	12V32Ah
PACKAGE SIZE(MM)	2300×1300×1300mm
LOADING QUANTITY(PCS)	40HQ : 18PCS
DRY WEIGHT, GROSS WEIGHT	490KG,555KG(680) 525KG,590KG(880/1000)



2026 **G3B** **THRAX**

# SW580L/680L/880L/1000L PRO

► ENGINE SW580L/680L/880L/1000L PRO

ENGINE TYPE Single-Cylinder, 4-Stroke Liquid-Cooled, 4 Valves (580/680)  
V-twin, water-cooled, 4-stroke, SOHC, 4 valves/cylinder (880/1000)

DISPLACEMENT 495CC/580CC/800CC/976CC

MAX POWER/RPM 29kw(6750±500r/Min)  
34kw/46hp@6500rpm  
50kW/68hp@7000rpm  
66kw/90hp@7200rpm

MAX TORQUE 44N·m(6000±500r/min)  
51N·m@6000rpm  
72N·m@6000rpm  
95N·m@6000rpm

FUEL SUPPLY Bosch Efi

TRANSMISSION Cvt

STARTING TYPE Electric Start

GEAR SHIFT /ORDER Manually/ L-H-N-R-P



580L PRO	680L PRO	880L PRO	1000L PRO
<b>40</b> HP	<b>46</b> HP	<b>68</b> HP	<b>90</b> HP
HORSEPOWER	HORSEPOWER	HORSEPOWER	HORSEPOWER

580L PRO	680/880/1000L PRO
<b>95</b> KM/H	<b>100</b> KM/H
MAX SPEED	MAX SPEED

► DIMENSIONS SW580L/680L/880L/1000L PRO

LENGTH X WIDTH X HEIGHT 2260×1230×1480mm (580/680)  
2300×1260×1495mm (880/1000)

WHEELBASE 1470mm

Seat Height 910mm

Front/Rear Track 990mm /940mm

GROUND CLEARANCE 290mm (580/680)  
300mm (880/1000)

► CHASSIS SW580L/680L/880L/1000L PRO

DRIVE SYSTEM 2WD/4WD/Front differential lock EPS

FRONT /REAR SUSPENSION Double A-arm independent suspension

Front/Rear Shock Absorber Hydraulic damping spring adjustable shock absorber (580/680)  
Adjustable nitrogen shock absorber (880/1000)

Front/Rear Brakes Front and rear hydraulic disc

FRONT TIRES, REAR TIRES 26×9-14, 26×11-14 (580/680)  
27×9-14, 27×11-14 (880/1000)

► OTHER FEATURES SW580L/680L/880L/1000L PRO

FUEL CAPACITY(L/GAL) 20L (580/680)  
25L (880/1000)

BATTERY CAPACITY 12V32Ah

PACKAGE SIZE(MM) 2300×1300×1300mm

LOADING QUANTITY(PCS) 40HQ : 18PCS

DRY WEIGHT, GROSS WEIGHT 430KG,500KG(580/680) 465KG,535KG(880/1000)



# 2026 **G3B** **THRAX** SW580S/680S PLUS

▶ ENGINE	SW580S/680S PLUS
ENGINE TYPE	Single-Cylinder , 4-Stroke Liquid-Cooled, 4 Valves
DISPLACEMENT	495CC/580CC
MAX POWER/RPM	29kw(6750±500r/Min) 34kw/46hp@6500rpm
MAX TORQUE	44N·m(6000±500r/min) 51N·m(6000r/min)
FUEL SUPPLY	Bosch Efi
TRANSMISSION	Cvt
STARTING TYPE	Electric Start
GEAR SHIFT /ORDER	Manually/ L-H-N-R-P



580S PLUS

**40**HP

HORSEPOWER

580S PLUS

**95** KM/H

MAX SPEED

680S PLUS

**46**HP

HORSEPOWER

680S PLUS

**100** KM/H

MAX SPEED

580/680S PLUS

**400**KG

DRY WEIGHT

580/680S PLUS

**460**KG

GROSS WEIGHT

▶ DIMENSIONS	SW580S/680S PLUS
LENGTH X WIDTH X HEIGHT	2130×1230×1270mm
WHEELBASE	1300mm
Seat Height	910mm
Front/Rear Track	990mm /940mm
GROUND CLEARANCE	290mm

▶ CHASSIS	SW580S/680S PLUS
DRIVE SYSTEM	2WD/4WD/Front differential lock EPS
FRONT /REAR SUSPENSION	Double A-arm independent suspension
Front/Rear Shock Absorber	Hydraulic damping spring adjustable shock absorber
Front/Rear Brakes	Front and rear hydraulic disc
FRONT TIRES, REAR TIRES	26x9-14 , 26x11-14
RIM	Front: 14x7.0 Rear: 14x8.5

▶ OTHER FEATURES	SW580S/680S PLUS
FUEL CAPACITY(L/GAL)	20L
BATTERY CAPACITY	12V32Ah
PACKAGE SIZE (MM)	2300x1300x1300mm
LOADING QUANTITY (PCS)	40HQ : 18PCS



2026 **GB3** **THRAX**

# SW580EL/680EL

▶ ENGINE	SW580EL/680EL
ENGINE TYPE	Single-Cylinder , 4-Stroke Liquid-Cooled, 4 Valves
DISPLACEMENT	495CC/580CC
MAX POWER/RPM	29kw(6750±500r/Min) 34kw/46hp@6500rpm
MAX TORQUE	44N·m(6000±500r/min) 51N·m(6000r/min)
FUEL SUPPLY	Bosch Efi
TRANSMISSION	Cvt
STARTING TYPE	Electric Start
GEAR SHIFT /ORDER	Manually/ L-H-N-R-P



580EL

**40**HP

HORSEPOWER

580EL

**95** KM/H

MAX SPEED

680EL

**46**HP

HORSEPOWER

680EL

**100** KM/H

MAX SPEED

580/680EL

**430** KG

DRY WEIGHT

580/680EL

**500** KG

GROSS WEIGHT

▶ DIMENSIONS	SW580EL/680EL
LENGTH X WIDTH X HEIGHT	2270x1250x1480mm
WHEELBASE	1470mm
Seat Height	900mm
Front/Rear Track	990mm /940mm
GROUND CLEARANCE	280mm

▶ CHASSIS	SW580EL/680EL
DRIVE SYSTEM	2WD/4WD/Front differential lock EPS
FRONT /REAR SUSPENSION	Double A-arm independent suspension
Front/Rear Shock Absorber	Hydraulic damping spring adjustable shock absorber
Front/Rear Brakes	Front and rear hydraulic disc
FRONT TIRES, REAR TIRES	25x8-12, 25x10-12
RIM	Front: 12x6.0 Rear:12x7.5

▶ OTHER FEATURES	SW580EL/680EL
FUEL CAPACITY(L/GAL)	20L
BATTERY CAPACITY	12V32Ah
PACKAGE SIZE (MM)	2300X1300x850mm
LOADING QUANTITY (PCS)	40HQ : 27PCS



# 2026 **GBB** **THRAX**

## SW580ES/680ES

▶ ENGINE	SW580ES/680ES
ENGINE TYPE	Single-Cylinder , 4-Stroke Liquid-Cooled, 4 Valves
DISPLACEMENT	495CC/580CC
MAX POWER/RPM	29kw(6750±500r/Min) 34kw/46hp@6500rpm
MAX TORQUE	44N·m(6000±500r/min) 51N·m(6000r/min)
FUEL SUPPLY	Bosch Efi
TRANSMISSION	Cvt
STARTING TYPE	Electric Start
GEAR SHIFT /ORDER	Manually/ L-H-N-R-P



580ES

**40**HP

HORSEPOWER

580ES

**95** KM/H

MAX SPEED

680ES

**46**HP

HORSEPOWER

680ES

**100** KM/H

MAX SPEED

580/680ES

**400**KG

DRY WEIGHT

580/680ES

**460**KG

GROSS WEIGHT

▶ DIMENSIONS	SW580ES/680ES
LENGTH X WIDTH X HEIGHT	2130×1230×1270mm
WHEELBASE	1300mm
Seat Height	900mm
Front/Rear Track	990mm /940mm
GROUND CLEARANCE	280mm

▶ CHASSIS	SW580ES/680ES
DRIVE SYSTEM	2WD/4WD/Front differential lock EPS
FRONT /REAR SUSPENSION	Double A-arm independent suspension
Front/Rear Shock Absorber	Hydraulic damping spring adjustable shock absorber
Front/Rear Brakes	Front and rear hydraulic disc
FRONT TIRES, REAR TIRES	25x8-12, 25x10-12
RIM	Front: 12x6.0 Rear:12x7.5

▶ OTHER FEATURES	SW580ES/680ES
FUEL CAPACITY(L/GAL)	20L
BATTERY CAPACITY	12V32Ah
PACKAGE SIZE (MM)	2300X1300X850mm
LOADING QUANTITY (PCS)	40HQ : 27PCS



2026 **FANGPOWER**

# SW580/680L-1 POWERMAX

▶ ENGINE	SW580/680L-1 POWERMAX
ENGINE TYPE	Single-Cylinder , 4-Stroke Liquid-Cooled, 4 Valves
DISPLACEMENT	495CC / 580CC
MAX POWER/RPM	29kw(6750±500r/Min) / 34kw(6500±500r/min)
MAX TORQUE	44N·m(6000±500r/min) / 51N·m(6000r/min)
FUEL SUPPLY	Bosch Efi
TRANSMISSION	Cvt
STARTING TYPE	Electric Start
GEAR SHIFT / ORDER	Manually / P-R-N-H-L



580L-1

**40**HP

HORSEPOWER

580L-1

**95** KM/H

MAX SPEED

680L-1

**46**HP

HORSEPOWER

680L-1

**100** KM/H

MAX SPEED

580/680L-1

**390**KG

DRY WEIGHT

580/680L-1

**460**KG

GROSS WEIGHT

▶ DIMENSIONS	SW580/680L-1 POWERMAX
LENGTH X WIDTH X HEIGHT	2200×1180×1270mm
WHEELBASE	1370mm
Seat Height	900mm
Front/Rear Track	970mm
GROUND CLEARANCE	310mm

▶ CHASSIS	SW580/680L-1 POWERMAX
DRIVE SYSTEM	2WD/4WD/Front differential lock
FRONT /REAR SUSPENSION	Double A-arm independent suspension
Front/Rear Shock Absorber	Coil spring+oil damping
Front/Rear Brakes	Four wheel hydraulic discs+ rear wheel parking
FRONT TIRES, REAR TIRES	25x8-12, 25x10-12
RIM	Front: 12×6.0 Rear: 12×8

▶ OTHER FEATURES	SW580/680L-1 POWERMAX
FUEL CAPACITY(L/GAL)	20/5.28
BATTERY CAPACITY	12V32Ah
PACKAGE SIZE (MM)	2300×1150×850mm
LOADING QUANTITY (PCS)	20FCL : 10PCS 40HQ : 30PCS



2026 **FANGPOWER**

# SW680 MUD POWERMAX

▶ ENGINE	SW680 MUD POWERMAX
ENGINE TYPE	Single-Cylinder , 4-Stroke Liquid-Cooled, 4 Valves
DISPLACEMENT	600cc
MAX POWER/RPM	34kw(6500±500r/min)
MAX TORQUE	51N·m(6000r/min)
FUEL SUPPLY	BOSCH EFI
TRANSMISSION	CVTECH CVT
STARTING TYPE	Electric start
GEAR SHIFT /ORDER	Manually/ P-R-N-H-L



680 MUD POWERMAX

**46** HP

HORSEPOWER

680 MUD POWERMAX

**100** KM/H

MAX SPEED

680 MUD POWERMAX

**390** KG

DRY WEIGHT

680 MUD POWERMAX

**460** KG

GROSS WEIGHT

▶ DIMENSIONS	SW680 MUD POWERMAX
LENGTH X WIDTH X HEIGHT	2200×1180×1270mm
WHEELBASE	1370mm
Seat Height	900mm
Front/Rear Track	970mm
GROUND CLEARANCE	280mm

▶ CHASSIS	SW680 MUD POWERMAX
DRIVE SYSTEM	2WD/4WD/Front differential lock, EPS
FRONT /REAR SUSPENSION	Double A-arm independent suspension
Front/Rear Shock Absorber	Coil spring + oil damping
Front/Rear Brakes	Four wheel hydraulic discs+ rear wheel parking
FRONT TIRES, REAR TIRES	25×8- 12, 25×10- 12
RIM	Front: 12×6.0 Rear: 12×8 cast aluminum

▶ OTHER FEATURES	SW680 MUD POWERMAX
FUEL CAPACITY(L/GAL)	20 / 5.28
BATTERY CAPACITY	12V32Ah
PACKAGE SIZE (MM)	2300x1150x1000mm
LOADING QUANTITY (PCS)	40HQ : 20PCS



# 2026 **FANGPOWER** SW250 BIG BULL

▶ ENGINE	SW250 BIG BULL
ENGINE TYPE	Oil-cooled
DISPLACEMENT	250cc
FUEL SUPPLY	Carburetor
TRANSMISSION	CVT
STARTING TYPE	Electric, Pull Start
GEAR SHIFT /ORDER	Manually/F-N-R



250 BIG BULL

**14.5** HP

HORSEPOWER

250 BIG BULL

**70** KM/H

MAX SPEED

250 BIG BULL

**210** KG

DRY WEIGHT

250 BIG BULL

**230** KG

GROSS WEIGHT

## ▶ DIMENSIONS SW250 BIG BULL

Length x Width x Height	1850×1130×1350mm
Seat height	840mm
Ground Clearance	140mm

## ▶ CHASSIS SW250 BIG BULL

Drive System	Chain-drive
Front brake	double disc brake
Rear brake	single hydraulic disc brake
Front Tires, Rear Tires	23/7.0-10, 22/10-10
Rim	Aluminium

## ▶ OTHER FEATURES SW250 BIG BULL

Fuel Capacity(L/gal)	4.5L
Battery capacity	12V/9A
Package size(mm)	1450x850x830mm
Loading Quantity(Pcs)	30pcs/20FT;63pcs/40'HQ



2026 **FANGPOWER**

# SW200 BIG BULL

► ENGINE SW200 BIG BULL

ENGINE TYPE	Oil-cooled
DISPLACEMENT	200cc
FUEL SUPPLY	Carburetor
TRANSMISSION	CVT
STARTING TYPE	Electric, Pull Start
GEAR SHIFT /ORDER	Manually/F-N-R



200 BIG BULL

**10.5** HP

HORSEPOWER

200 BIG BULL

**70** KM/H

MAX SPEED

200 BIG BULL

**177** KG

DRY WEIGHT

200 BIG BULL

**197** KG

GROSS WEIGHT

► DIMENSIONS SW200 BIG BULL

Length x Width x Height	1730×1080×1130mm
Seat height	815mm
Ground Clearance	130mm

► CHASSIS SW200 BIG BULL

Drive System	Chain-drive
Front brake	double disc brake
Rear brake	single hydraulic disc brake
Front Tires, Rear Tires	23/7.0-10, 22/10-10
Rim	Aluminium

► OTHER FEATURES SW200 BIG BULL

Fuel Capacity(L/gal)	4.5L
Battery capacity	12V/9A
Package size(mm)	1460×860×750mm
Loading Quantity(Pcs)	30pcs/20FT;63pcs/40'HQ



2026 **FANGPOWER**

# SW125-1 OUTLAW/125-2 MARS/ 125-3 SPORT

▶ ENGINE	SW125-1 OUTLAW/125-2 MARS/125-3 SPORT
ENGINE TYPE	4 stroke,air cooled
DISPLACEMENT	125cc
FUEL SUPPLY	Carburetor
TRANSMISSION	CVT
STARTING TYPE	Electric start
GEAR SHIFT /ORDER	Manually/F-N-R



125-1 OUTLAW

**50** KM/H **102** KG **122** KG  
MAX SPEED DRY WEIGHT GROSS WEIGHT

125-2 MARS

**60** KM/H **108** KG **120** KG  
MAX SPEED DRY WEIGHT GROSS WEIGHT

125-3 SPORT

**60** KM/H **95** KG **110** KG  
MAX SPEED DRY WEIGHT GROSS WEIGHT

▶ DIMENSIONS	SW125-1 OUTLAW/125-2 MARS/125-3 SPORT
Length x Width x Height	1480×1040×950mm (SW125-1) 1400×900×1040mm (SW125-2) 1530×930×980mm (SW125-3)
Seat height	700mm/720mm/720mm
Ground Clearance	110mm/115mm/115mm

▶ CHASSIS	SW125-1 OUTLAW/125-2 MARS/125-3 SPORT
Drive System	Chain-drive
Front brake	double hydraulic disc brake
Rear brake	single hydraulic disc brake
Front Tires/Rear Tires	18×7-8/18×9-8 (SW125-1) 19/7.0-8 / 18/9.5-8 (SW125-2/SW125-3)
Rim	Steel

▶ OTHER FEATURES	SW125-1 OUTLAW/125-2 MARS/125-3 SPORT
Fuel Capacity(L/gal)	3L
Battery capacity	12V5A
Package size (mm)	1390×905×630mm (SW125-1) 1290×750×650mm (SW125-2/SW125-3)
Loading Quantity(Pcs)	84pcs/40'HQ (SW125-1) 36pcs/20FT; 108pcs/40'HQ (SW125-2/SW125-3)



2026 **FANGPOWER**

# FX400 PREDATOR

▶ ENGINE	FX400 PREDATOR
ENGINE TYPE	4-stroke, Single-Cylinder, Water-cooled
DISPLACEMENT	400cc
MAX POWER/RPM	18kw/6500rpm
FUEL SUPPLY	EFI/Carburetor
TRANSMISSION	CVT
STARTING TYPE	Electric start
GEAR SHIFT /ORDER	Manually/F-N-R



400 PREDATOR

**25** HP

HORSEPOWER

400 PREDATOR

**75** KM/H

MAX SPEED

400 PREDATOR

**380** KG

DRY WEIGHT

400 PREDATOR

**480** KG

GROSS WEIGHT

▶ DIMENSIONS	FX400 PREDATOR
Length x Width x Height	2700×1450×1750mm
Wheelbase	1980mm
Front Tread	1250mm
Rear Tread	1150mm
Ground Clearance	300mm

▶ CHASSIS	FX400 PREDATOR
Drive System	Shaft-Drive
Front Suspension	Double A-arm Suspension
Rear Suspension	Fang power 4-Link® bar Rear Suspension
Front Tires, Rear Tires	25×8-12, 25×10-12
Rim	Front: 12×6.0 Rear: 12×8 cast aluminum

▶ OTHER FEATURES	FX400 PREDATOR
Fuel Capacity(L/gal)	9.5L (2.1 Gallon)
Battery capacity	6DM14 12V12AH
Package size(mm)	2290×1400×815mm
Loading Quantity (Pcs)	8units/20"; 24units/40HQ



2026 **FANGPOWER**

# FX400XL PREDATOR

▶ ENGINE	FX400XL PREDATOR
ENGINE TYPE	4-stroke, Single-Cylinder, Water-cooled
DISPLACEMENT	400cc
MAX POWER/RPM	18kw/6500rpm
FUEL SUPPLY	EFI/Carburetor
TRANSMISSION	CVT
STARTING TYPE	Electric start
GEAR SHIFT /ORDER	Manually/F-N-R



400XL PREDATOR

**25** HP

HORSEPOWER

400XL PREDATOR

**75** KM/H

MAX SPEED

400XL PREDATOR

**480** KG

DRY WEIGHT

400XL PREDATOR

**540** KG

GROSS WEIGHT

▶ DIMENSIONS	FX400XL PREDATOR
Length x Width x Height	3360×1450×1750mm
Wheelbase	2800mm
Front Tread	1250mm
Rear Tread	1150mm
Ground Clearance	300mm

▶ CHASSIS	FX400XL PREDATOR
Drive System	Shaft-Drive
Front Suspension	Double A-arm Suspension
Rear Suspension	Fang power 4-Link® bar Rear Suspension
Front Tires, Rear Tires	25×8-12, 25×10-12
Rim	Front: 12×6.0 Rear: 12×8 cast aluminum

▶ OTHER FEATURES	FX400XL PREDATOR
Fuel Capacity(L/gal)	9.5L (2.1 Gallon)
Battery capacity	6DM14 12V12AH
Package size(mm)	2980×1400×815mm
Loading Quantity (Pcs)	12units/40HQ



# 2026 **FANGPOWER** FX400U FARMER

▶ ENGINE	FX400U FARMER
ENGINE TYPE	4-stroke, Single-Cylinder, Water-cooled
DISPLACEMENT	400cc
MAX POWER/RPM	18kw/6500rpm
FUEL SUPPLY	EFI/Carburetor
TRANSMISSION	CVT
STARTING TYPE	Electric start
GEAR SHIFT /ORDER	Manually/F-N-R



400U FARMER

**25** HP

HORSEPOWER

400U FARMER

**75** KM/H

MAX SPEED

400U FARMER

**440** KG

DRY WEIGHT

400U FARMER

**540** KG

GROSS WEIGHT

▶ DIMENSIONS	FX400U FARMER
Length x Width x Height	2700×1450×1750mm
Wheelbase	1980mm
Front Tread	1250mm
Rear Tread	1150mm
Ground Clearance	300mm

▶ CHASSIS	FX400U FARMER
Drive System	Shaft-Drive
Front Suspension	Double A-arm Suspension
Rear Suspension	Fang power 4-Link® bar Rear Suspension
Front Tires, Rear Tires	25×8-12, 25×10-12
Rim	Front: 12×6.0 Rear: 12×8 cast aluminum

▶ OTHER FEATURES	FX400U FARMER
Fuel Capacity(L/gal)	9.5L (2.1 Gallon)
Battery capacity	6DM14 12V12AH
Package size(mm)	2290×1410×1260mm
Loading Quantity (Pcs)	4units/20"; 16units/40HQ



2026 **FANGPOWER**

# FX400 SNOWMOBILE

▶ ENGINE	FX400 SNOWMOBILE
ENGINE TYPE	4-stroke, Single-Cylinder, Water-cooled
DISPLACEMENT	400cc
MAX POWER/RPM	18kw/6500rpm
FUEL SUPPLY	EFI/Carburetor
TRANSMISSION	CVT
STARTING TYPE	Electric start
GEAR SHIFT /ORDER	Manually/F-N-R



400 SNOWMOBILE

**25** HP

HORSEPOWER

400 SNOWMOBILE

**75** KM/H

MAX SPEED

400 SNOWMOBILE

**500** KG

DRY WEIGHT

400 SNOWMOBILE

**560** KG

GROSS WEIGHT

▶ DIMENSIONS	FX400 SNOWMOBILE
Length x Width x Height	3250×1520×1750mm
Wheelbase	1980mm
Front Tread	1380mm
Rear Tread	1520mm
Ground Clearance	300mm

▶ CHASSIS	FX400 SNOWMOBILE
Drive System	Shaft-Drive
Front Suspension	Double A-arm Suspension
Rear Suspension	Fang power 4-Link® bar Rear Suspension

▶ OTHER FEATURES	FX400 SNOWMOBILE
Fuel Capacity(L/gal)	9.5L (2.1 Gallon)
Battery capacity	6DM14 12V12AH
Package size(mm)	2980×1400×815mm
Loading Quantity(Pcs)	2units/20"; 16units/40HQ



# 2026 **FANGPOWER** FX250-2 SPIDER

▶ ENGINE	FX250-2 SPIDER
ENGINE TYPE	4-stroke, Single-Cylinder, Air/Oil-cooled
DISPLACEMENT	250cc
MAX POWER/RPM	10.5kw(7500r/min)
FUEL SUPPLY	Carburetor
TRANSMISSION	CVT
STARTING TYPE	Electric start
GEAR SHIFT /ORDER	Manually/F-N-R



250-2 SPIDER

**14.5** HP

HORSEPOWER

250-2 SPIDER

**60** KM/H

MAX SPEED

250-2 SPIDER

**380** KG

DRY WEIGHT

250-2 SPIDER

**480** KG

GROSS WEIGHT

▶ DIMENSIONS	FX250-2 SPIDER
Length x Width x Height	2590×1350×1750mm
Wheelbase	1980mm
Front Tread	1150mm
Rear Tread	1040mm
Ground Clearance	260mm

▶ CHASSIS	FX250-2 SPIDER
Drive System	Shaft-Drive
Front Suspension	Double A-arm Suspension
Rear Suspension	Fang power 4-Link® bar Rear Suspension
Front Tires, Rear Tires	25×8-12, 25×10-12
Rim	Front: 12×6.0 Rear: 12×8 cast aluminum

▶ OTHER FEATURES	FX250-2 SPIDER
Fuel Capacity(L/gal)	9.5L (2.1 Gallon)
Battery capacity	6DM14 12V12AH
Package size(mm)	2290×1300×815mm
Loading Quantity (Pcs)	8units/20"; 18units/40"; 24units/40HQ



# 2026 **FANGPOWER** FX250 DICTATOR

▶ ENGINE	FX250 DICTATOR
ENGINE TYPE	4-stroke, Single-Cylinder, Air/Oil-cooled
DISPLACEMENT	250cc
MAX POWER/RPM	10.5kw(7500r/min)
FUEL SUPPLY	EFI/Carburetor
TRANSMISSION	CVT
STARTING TYPE	Electric start
GEAR SHIFT /ORDER	Manually/F-N-R



250 DICTATOR

**14.5** HP

HORSEPOWER

250 DICTATOR

**60** KM/H

MAX SPEED

250 DICTATOR

**280** KG

DRY WEIGHT

250 DICTATOR

**360** KG

GROSS WEIGHT

▶ DIMENSIONS	FX250 DICTATOR
Length x Width x Height	2450×1270×1670mm
Wheelbase	1885mm
Front Tread	1020mm
Rear Tread	1000mm
Ground Clearance	180mm

▶ CHASSIS	FX250 DICTATOR
Drive System	Chain-drive
Front Suspension	Double A-arm optional
Rear Suspension	Dual Shock Swing arm
Front Tires, Rear Tires	21×7-10, 22×10-10
Rim	Front: 10×5.5 Rear: 10×8 cast aluminum

▶ OTHER FEATURES	FX250 DICTATOR
Fuel Capacity(L/gal)	9.5L (2.1 Gallon)
Battery capacity	6MF9 12V9Ah
Package size(mm)	2290×1300×815mm
Loading Quantity (Pcs)	8units/20"; 18units/40"; 26units/40HQ



2026 **FANGPOWER**

# FX200 TIGER

▶ ENGINE	FX200 TIGER
ENGINE TYPE	4-stroke, Single-Cylinder, Air/Oil-cooled
DISPLACEMENT	200cc
MAX POWER/RPM	7.6kw(7000r/min)
FUEL SUPPLY	Carburetor
TRANSMISSION	CVT
STARTING TYPE	Electric start
GEAR SHIFT /ORDER	Manually/F-N-R



200 TIGER

**10.5** HP

HORSEPOWER

200 TIGER

**55** KM/H

MAX SPEED

200 TIGER

**290** KG

DRY WEIGHT

200 TIGER

**360** KG

GROSS WEIGHT

▶ DIMENSIONS	FX200 TIGER
Length x Width x Height	2450×1270×1670mm
Wheelbase	1860mm
Front Tread	1020mm
Rear Tread	965mm
Ground Clearance	152mm

▶ CHASSIS	FX200 TIGER
Drive System	Chain-drive
Front Suspension	Double A-arm optional
Rear Suspension	Dual Shock Swing arm
Front Tires, Rear Tires	21×7-10, 22×10-10 ALUMINUM RIM
Rim	Front: 10×5.5 Rear: 10×8 cast aluminum

▶ OTHER FEATURES	FX200 TIGER
Fuel Capacity(L/gal)	9.5L (2.1 Gallon)
Battery capacity	6MF9 12V9Ah
Package size(mm)	2290×1300×815mm
Loading Quantity (Pcs)	8units/20"; 18units/40"; 26units/40HQ



# 2026 **FANGPOWER** EV POWERMAX

ENGINE	EV POWERMAX
Power Type (kw)	72V 7.5 DC PM Motor
Controller	72V 400A Programmable Multi-Mode Controller
On-board charger	100-240V AC input; 72V/17A DC output
Battery	Lithium Iron Phosphate 76.8V 100Ah
Protection class of battery pack	IP67
Controller communication	CAN2.0
Starting type	Electric start
Gear shift /order	Manually/F-N-R



EV POWERMAX

**100** KM

RECHARGE MILEAGE

EV POWERMAX

**85** KM/H

MAX SPEED

EV POWERMAX

**420** KG

DRY WEIGHT

EV POWERMAX

**490** KG

GROSS WEIGHT

DIMENSIONS	EV POWERMAX
LENGTH X WIDTH X HEIGHT	2200×1180×1270mm
WHEELBASE	1370mm
Seat Height	900mm
Front/Rear Track	970mm
GROUND CLEARANCE	280mm

CHASSIS	EV POWERMAX
Drive System	Selectable 4×2 / 4×4 / 4×4-lock
Front/Rear Suspension	Double A-arm independent suspension
Front/Rear Shock Absorber	Coil spring + oil damping
Front/Rear Brakes	Dual hydraulic disc/Single hydraulic disc
Front Tires, Rear Tires	ATV 25×8- 12, ATV 25×10- 12
Rim	Front: 12×6.0 Rear: 12×8 cast aluminum

OTHER FEATURES	EV POWERMAX
Battery capacity	72V100Ah
Package size(mm)	2300×1150×850mm
Loading Quantity(Pcs)	20FCL : 10PCS 40HQ : 30PCS



# 2026 FANGPOWER EV PREDATOR

ENGINE	EV PREDATOR
Power Type (kw)	72V 5kw DC PM Motor
Controller	72V 300A Programmable Multi-Mode Controller
On-board charger	100-240V AC input; 72V/17A DC output CAN2.0
Battery	Lithium Iron Phosphate 76.8V 100Ah
Protection class of battery pack	IP67
Controller communication	CAN2.0
Starting type	Electric start
Gear shift /order	Manually/F-N-R



EV PREDATOR

**100** KM

RECHARGE MILEAGE

EV PREDATOR

**75** KM/H

MAX SPEED

EV PREDATOR

**410** KG

DRY WEIGHT

EV PREDATOR

**510** KG

GROSS WEIGHT

DIMENSIONS	EV PREDATOR
Length x Width x Height	2700×1450×1750mm
Wheelbase	1980mm
Front Tread	1250mm
Rear Tread	1150mm
Ground Clearance	300mm

CHASSIS	EV PREDATOR
Drive System	Shaft-Drive
Front Suspension	Double A-arm Suspension
Rear Suspension	Fang power 4-Link® bar Rear Suspension
Front Tires, Rear Tires	25×8-12, 25×10-12
Rim	Front: 12×6.0 Rear: 12×8 cast aluminum

OTHER FEATURES	EV PREDATOR
Battery capacity	12V12AH
Package size (mm)	2290×1400×815mm
Loading Quantity (Pcs)	8units/20"; 24units/40HQ



# 2026 **GBB** SW400/500/600CC

▶ ENGINE	400CC
ENGINE TYPE	Single-cylinder, water-cooled, 4-stroke, SOHC, 4 valves
BORE X STROKE (MM)	91×61.5
COMPRESSION RATIO	10.3:1
RPM	30.6hp @ 7200rpm
MAX TORQUE	33N·m @ 6000rpm
TRANSMISSION	CVT
STARTING TYPE	Electric Start
OIL CAPACITY	2600ml
NET WEIGHT	58.2KG



400CC

**400**cc

DISPLACEMENT

**22.5**kw

MAX POWER

500CC

**495**cc

DISPLACEMENT

**29**kw

MAX POWER

600CC

**580**cc

DISPLACEMENT

**34**kw

MAX POWER

▶ ENGINE	500CC
ENGINE TYPE	Single-cylinder, water-cooled, 4-stroke, SOHC, 4 valves
BORE X STROKE (MM)	91×76.2
COMPRESSION RATIO	10.3:1
RPM	40hp(6750±500r/Min)
MAX TORQUE	44N·m(6000±500r/min)
TRANSMISSION	CVT
STARTING TYPE	Electric Start
OIL CAPACITY	2600ml
NET WEIGHT	62.5KG

▶ ENGINE	600CC
ENGINE TYPE	Single-cylinder, water-cooled, 4-stroke, SOHC, 4 valves
BORE X STROKE (MM)	91×89.2
COMPRESSION RATIO	10.5:1
RPM	46hp@6500rpm
MAX TORQUE	51N·m(6000r/min)
TRANSMISSION	CVT continuously variable transmission+(L-H-N-R-P)
STARTING TYPE	Electric Start
OIL CAPACITY	2600ml
NET WEIGHT	62.5KG



# 2026 **G3B** SW800/1000CC

▶ ENGINE	800CC
ENGINE TYPE	V-twin, water-cooled, 4-stroke, SOHC, 4 valves/cylinder
BORE X STROKE (MM)	91×61.5
COMPRESSION RATIO	10.6:1
RPM	68hp@7000rpm
MAX TORQUE	72N·m@6000rpm
TRANSMISSION	CVT
STARTING TYPE	Electric Start
OIL CAPACITY	2000mL
NET WEIGHT	74KG



800CC

**800**cc  
DISPLACEMENT

1000CC

**976**cc  
DISPLACEMENT

800CC

**50**kw  
MAX POWER

1000CC

**66**kw  
MAX POWER

▶ ENGINE	1000CC
ENGINE TYPE	V-twin, water-cooled, 4-stroke, SOHC, 4 valves/cylinder
BORE X STROKE (MM)	91×75
COMPRESSION RATIO	10.6:1
RPM	90hp@7200rpm
MAX TORQUE	95N·m@6000rpm
TRANSMISSION	CVT
STARTING TYPE	Electric Start
OIL CAPACITY	2000mL
NET WEIGHT	78KG

